



- Up to 21 ppm print speed
- Built-in auto duplexing
- 1200 x 1200 dpi
- 2151N is network-ready
- 2152W is wireless and network-ready
- 600 sheets input, 250 sheets output
- 100,000 pages per month duty cycle
- TonerSave extends cartridge life up to 40%
- Upgradable memory
- Compatible with Windows, Macintosh, Linux

Fast. Hard-working. Expandable. We're talking about your business. And we have just the printers you need. Our 2150-series printers can handle everything a small to medium-sized business can throw at them, and then some. Fast 21 ppm print speeds. Broad compatibility. Professional quality. Samsung durability. Our printers work as hard as you do.

ML-2150/2151N/ 2152W

Workgroup Monochrome Laser Printers

Note: Macintosh print resolution is limited to 600 dpi unless optional PostScript emulation is installed. Macintosh network printing requires 10/100 Base TX card and PostScript emulation.



ML-2150/2151N/2152W



Workgroup 21 ppm Monochrome Laser Printers

Specifications	ML-2150	ML-2151N	ML-2152W
Technology	Laser	Laser	Laser
Print Speed (Up To)	21 ppm, 10 ppm Duplex	21 ppm, 10 ppm Duplex	21 ppm, 10 ppm Duplex
First Page Out	12 Sec.	12 Sec.	12 Sec.
Duplexing	Automatic, Built-In Unit	Automatic, Built-In Unit	Automatic, Built-In Unit
Processor	166 MHz RISC	166 MHz RISC	166 MHz RISC
Memory, Standard	16 MB	16 MB	16 MB
Memory, Maximum	144 MB	144 MB	144 MB
Print Language, Standard	PCL 6, GDI, IBM ProPrinter, Epson	PCL 6, GDI, PS 3, IBM ProPrinter, Epson	PCL 6, GDI, PS 3, IBM ProPrinter, Epson
Print Language, Optional	PS 3	N/A	N/A
Print Resolution	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi
Connectivity, Standard	Hi-Speed USB 2.0, IEEE-1284 Parallel	Hi-Speed USB 2.0, IEEE-1284 Parallel, 10/100 Base TX	Hi-Speed USB 2.0, IEEE-1284 Parallel, 10/100 Base TX, 802.11b Wireless LAN
Connectivity, Optional	10/100 Base TX, 802.11b Wireless LAN	802.11b Wireless LAN	N/A
Paper Size	3" x 5" to 8.5" x 14"	3" x 5" to 8.5" x 14"	3" x 5" to 8.5" x 14"
Paper Input Capacity, Standard (Tray 1, Bypass)	500 Sheets, 100 Sheets	500 Sheets, 100 Sheets	500 Sheets, 100 Sheets
Paper Input Capacity, Optional	500 Sheets	500 Sheets	500 Sheets
Paper Output Capacity, Standard (Face-Down, Face-Up)	250 Sheets, 100 Sheets	250 Sheets, 100 Sheets	250 Sheets, 100 Sheets
Microsoft® Windows	MS Windows 95, 98, Me, NT4, 2000, XP	MS Windows 95, 98, Me, NT4, 2000, XP	MS Windows 95, 98, Me, NT4, 2000, XP
Apple® Mac OS	Classic, OS X 10, 10.1, 10.2	Classic, OS X 10, 10.1, 10.2	Classic, OS X 10, 10.1, 10.2
Linux	Red Hat, Caldera, Debian, Mandrake, Slackware, Turbolinux, SuSE	Red Hat, Caldera, Debian, Mandrake, Slackware, Turbolinux, SuSE	Red Hat, Caldera, Debian, Mandrake, Slackware, Turbolinux, SuSE
Standard Font (Scalable, Bitmap, TrueType)	45, 1, 136	45, 1, 136	45, 1, 136
Acoustics (Printing, Standby)	52 dB, 35 dB	52 dB, 35 dB	52 dB, 35 dB
Power Consumption (Printing, Power Save)	350 Watts, 15 Watts	350 Watts, 15 Watts	350 Watts, 15 Watts
Monthly Duty Cycle	100,000 Pages	100,000 Pages	100,000 Pages
Dimensions (W x D x H)	14.3" x 16.1" x 11.6"	14.3" x 16.1" x 11.6"	14.3" x 16.1" x 11.6"
Weight	24.3 Lbs.	27.3 Lbs.	27.3 Lbs.
Toner Part Number	ML-2150D8/XAA	ML-2150D8/XAA	ML-2150D8/XAA
Toner Yield at 5% Coverage (Standard, Starter)	8,000 Pages, 4,000 Pages	8,000 Pages, 4,000 Pages	8,000 Pages, 4,000 Pages
Second Paper Cassette	ML-2150S5/XAA (500 Sheets)	ML-2150S5/XAA (500 Sheets)	ML-2150S5/XAA (500 Sheets)
Network Solution	ML-00NB/XAA	Standard Feature	Standard Feature
PostScript 3 Upgrade	ML-00PB/XAA	Standard Feature	Standard Feature
Memory Upgrade	Samsung 100-pin SDRAM (32 MB & 128 MB Modules)	Samsung 100-pin SDRAM (32 MB & 128 MB Modules)	Samsung 100-pin SDRAM (32 MB & 128 MB Modules)

Note: Macintosh print resolution is limited to 600 dpi unless optional PostScript emulation is installed. Macintosh network printing requires 10/100 Base TX card and PostScript emulation.

Product Support: 1-800-SAMSUNG
 Product Information: 1-866-542-7214 or www.samsungusa.com/printer
 Competitive Comparison: www.samsungpartner.com/comparison

©2003 Samsung Electronics America, Inc. Specifications and design are subject to change without notice. Non-metric weights and measurements are approximate. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies.

