



- Fast print and copy speeds up to 22 ppm/cpm
- USB Direct interface for computer-free printing, scanning
- Money-saving PowerSave, PaperSave, TollSave and TonerSave modes
- Easy to use ID Card copy function
- Simple to use Scan-to-Email function
- Fast 33.6Kbps fax modem, approximately 3-second transmission speed
- Color scanning, up to 4800 x 4800 dpi (enhanced mode)

Combine and conquer. The Samsung fax-enabled SCX-4720F laser multifunction machine delivers sophisticated document functionality in a smarter, simpler package. With fast print speeds. Fast connectivity. Fast 33.6Kbps fax modem for quick 3 second/page transmission. One-touch features and more. So you never have to sacrifice productivity for convenience. And with the category's first USB Direct interface, you can use a USB memory device to scan, print, upload or download without a computer. The Samsung SCX-4720F. Print, copy, scan and so much more.

SCX-4720F

Laser Printer, Digital Copier,
Color Scanner and Laser Fax




SCX-4720F



Laser Multifunction Machines

Specifications	
Laser Printer	
Technology	Laser
Speed ¹	Up to 22 ppm
FPOT	10 Seconds (From Standby Mode)
Resolution	Up to 1200 dpi
Printer Memory (Standard, Max)	32 MB, 160 MB
Print Language/Emulation	PCL 6
Supported OS	Windows 98, Me, 2000, XP, NT 4.0, Various Linux Systems (Via USB Only)
Laser Fax (SCX-4720F Only)	
Modem Speed	33.6Kbps
Transmission Speed ²	Approx. 3 Seconds Per Page
Scan Speed ³	Platen: Approx. 2 Seconds, ADF: Approx. 4 Seconds
Compatibility	ITU-T Group 3, ECM
Coding Method	MH/MR/MMR/JBIG/JPEC
Memory	16 MB Standard/128 MB Maximum
Auto Dial	200 Speed Dial, 40 One-Touch
Digital Copier	
Copy Speed ⁴	Up to 22 cpm
FCOT	10 Seconds (From Standby Mode)
Resolution	600 x 600 dpi
Reduction/Enlargement	25 – 400%
Multiple Copy	1 – 99 Copies
Color Scanner	
Type	Flatbed
Method	Color CCD
Resolution (Optical, Enhanced)	Up to 600 x 1200 dpi, 4800 x 4800 dpi
Scan Size	Platen: 8.2" x 11.7", ADF: 8.2" x 14"
Bit Depth	Color: 36-Bit (Internal), 24-Bit (External), Black: 1-Bit (Text Mode), 8-Bit (Gray Mode)
Grayscale	256 Levels
Compatibility	Twain Standard, WIA Standard
Paper Handling	
Input	Standard: 250-Sheet Cassette and 50-Sheet Auto Document Feeder (ADF) Optional: 250-Sheet Second Paper Cassette
Multipurpose Tray	10 Sheets
Output Tray	150 Sheets Face Down, 1 Sheet Face Up
Media Types	Tray: Plain Paper Manual Tray: Plain Paper, Transparency, Label, Post Card, Envelope
Media Size	Print, Tray: Letter, A4, Legal, Folio, Executive, B5, A5, A6 (4.1" x 5.8" ~ 8.5" x 14") Print, Manual Tray: Letter, A4, Legal, Folio, Executive, B5, A5, A6, Envelopes 6-3/4, 7-3/4, #9, #10, DL, C5, B5 (3" x 5" ~ 8.5" x 14") Fax and Copy: Letter, Legal
Paper Weight	Cassette: 16 – 24 Lbs., Bypass: 16 – 43 Lbs.
Consumables	
Toner Type	1 Piece Integrated Toner and Drum Unit
Toner Yield ⁵	Approx. 3,000 Pages @ 5% Coverage (SCX-4720D3/XAA)
TonerSave Mode	Approx. 5,000 pages @ 5% Coverage (SCX-4720D5/XAA) Increases Toner Yield Up to 40%
General	
Connectivity	Standard: USB 2.0, IEEE-1284 Parallel, Optional: 10/100Base-TX, 802.11b Wireless LAN
Power	110 – 127 VAC, 50/60 Hz
Power Consumption (Normal, Standby, Sleep)	300 W, XX W , 10 W (ENERGY STAR [®] Compliant)
Monthly Duty Cycle	Up to 15,000 Pages
Safety Certification	UL Safety
Operating Environment	Temperature: 50° – 89°F, Relative Humidity: 20 – 80%
Dimensions (W x D x H)	18.7" x 17.2" x 16.4"
Weight	28.7 Lbs.



Product Information
1-866-542-7214

Product Support
1-800-SAMSUNG

www.samsungusa.com/mfp

©2004 Samsung Electronics America, Inc. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. All applicable specifications based on letter-size paper with 5% coverage. ¹Print speeds (pages per minute) may vary due to various factors including complexity and graphics size, I/O configuration, computer configuration, amount of RAM at the printer, network operating system, network configuration and printer color calibration. ²Fax transmission speed measured with ITU-T No. 1 Chart (Phase C) at standard resolution, MMR (JBIG) coding, 33.6Kbps, memory transmission, ECM. ³Fax scan speed measured with ITU-T No. 1 chart at standard resolution. ⁴Copy speed is measured by multiple-copy output of a single document. ⁵Toner and drum yield figures may be affected by operating environment, printing interval, color/black, media type and media size. Non-metric weights and measurements are approximate. All specifications are subject to change without notice and provided "as is" with no warranty. Samsung shall not be liable for any direct, indirect, special, incidental, or consequential damages in connection with the use of this material. SCX4720F11/04r1

